

TT-DVR5416

16 CH DVR



SPECIFICATIONS:

DVR Type	16 Channel DVR	
Model	TT-DVR5416	
System	Operating system	LINUX real-time operating system
Video parameter		
	Video compression standard	H.264
	Preview resolution	PAL:704X576 (D1) level: 500 vertical lines: 450
	Playback resolution	PAL:352X288(CIF) NTSC ~320X240 ~CIF)
	Video input	16CH
	Video output	1 VGA 1024X768 1 1440X900 1280X1024 output, support TV output (RCA or BNC interface 1.0Vp-p75 ohm, HDMI
	Support system	PAL/NTSC/SECAM
	Video frame rate	The 25 frame / sec / channel (PAL) 1.3.6.12.25
		The 30 frame / sec / channel (NTSC) 1.3.7.15.30
		Support user defined
	Video output rate	32kbps 2048kbps
	Auxiliary video coding	CIF:352X288(PAL) 320x240(NTSC)
	Auxiliary output rate	CIF:1-15 32kbps 512Kbps / stream
	Capture	/
Audio parameter		
	Audio compression standard	ADPCM
	Audio input	4 RCA 2Vp-p 600 ohm input socket
	Audio output	1 road output RCA socket 2Vp-p 600 ohm
	Intercom voice input	/
	Output sampling rate	8KHZ
	Sampling size	16
	Number of channels	Mono
	Data rate	32kbps
Hard disk drive		
	Type	1 SATA interface
	Maximum capacity	2 SATA interface maximum support 2TB hard disk
Video management		
	Video mode	Manual, timed, motion detection, alarm recording
	The video recording preservation	The machine hard disk, network
	Video playback	8 way at the same time playback, support 1.4, 8 split screen
	Backup mode	This machine mobile hard disk U disk DVD network
External interface		
	Network interface	1 10M/100M adaptive Ethernet interface
	Serial interface	1 RS232 port
	USB interface	2 USB interface
	Keyboard interface	/
	Console interface	1 RS422 interface
	Alarm input	4 Input
	Alarm output	1 Output
Other	Power supply	DC 12V/4A
	Power waste	14W Not connected hard disk
	Working humidity	10%-90%RH
	Chassis	1.5U
	Size	315mmX250mmX45mm
	Installation test	Rack mounting, desktop installation

NOTE: ADINO TELECOM LTD reserves the right, without notification, to make changes in product design or specifications