

TT-HLSO60CO-S

600TVL Indoor IR Dome Camera

Key Features:

- Sony 1/3" super HAD
- 3.6mm board lens
- 24pcs Φ 5 IR LEDs, IR distance:25m
- 3-Axis Cable Through Bracket Included. D-WDR



Specifications :

Model	TT-HLSO60CO-S
TV Systems	NTSC / PAL
CCD	Sony 1/3"super HAD
Effective Pixels	380K(768H *494V) / 440K(752H *582V)
Sensing Area	6.35UM*7.4UM / 6.5UM*6.25UM
Electronic Shutter	1/60 to 1/100,000 / 1/50 to 1/100,000
Flickerfree	On/Off
Resolution	600 TV Lines (Max.) / 650TV Lines(B/W)
Lens	3.6mm board lens
LED	24pcs Φ 5 IR LEDs
IR Distance	25m
Minimum Illumination	AGC/ Color: 0.1 Lux (F2.0) / B/W : 0.01 Lux (F2.0)
Video Output	Video Output 1.0Vp~p/ 75ohm
Gamma Correction	0.45
S/N	50dB(AGC OFF)
Digital Wide Dynamic Range	On / Off
OSD Display	Chinese/English
Privacy Masking	4 Windows
Day & Night	Color/ B/W/ Auto
Motion Detection	On / Off (4 programmable zones)
Synchronization	Internal
White Balance	WB1/ WB2/ WB setup/ Manual WB
Mirror Function	YES (Left/Right)
DNR(Digital Noise Reduce)	(2D-NR)
BLC	BLC/HBLC/Off
AGC (Auto Gain Control)	On/Off (Horizontal Setup)
Remote Communication	RS-485 PELCO D/P
Working Temperature & Humidity	-10°C to 50°C /30% to 80%
Storage Temperature & Humidity	-30°C to 60°C /20% to 90%
Power(Maximum)	DC12V \pm 10%, < 1Watts
Body Size	75mm (H) x 93mm (W)

NOTE: ADINO TELECOM LTD reserves the right, without notification, to make changes in product design or specifications