

# TT-HLSO70EVP-F

## 700TVL 35m Outdoor IR Dome

### Key Features:

- Color 1/3 Sony EFFIO E CCD DSP 700TVL
- 3.6 mm fix Lens
- 36pcs of 5 IR LEDs, IR distance:35m
- Preset OSD Menu (8 Languages)
- Motion Detection



### Specifications:

| Model                          | TT-HLSO70EVP-F                                               |
|--------------------------------|--------------------------------------------------------------|
| TV Systems                     | PAL / NTSC                                                   |
| Image Sensor                   | Color 1/3" Sony Ex-view CCD II EFFIO~E DSP (960H)            |
| Effective Pixels               | 570K (976H*582V) / 480K (976H*494V)                          |
| Resolution / DSP               | Color: 700TVL; B/W: 750TVL / Sony Enhanced EFFIO~E           |
| Minimum Illumination           | Color: 0.01 Lux (F1.2) B/W: 0.001 Lux (F1.2)                 |
| IR LEDs (pcs)                  | 36pcs-5 IR LEDs                                              |
| Effective Distance             | 35m                                                          |
| Lens (mm)                      | 3.6mm fix Lens                                               |
| Wide Dynamic Range             | D-WDR (ATR)                                                  |
| OSD MENU                       | With OSD Menu Control Cable                                  |
| Video Output                   | 1.0Vp-p/ Composite Output, 75ohm (BNC)                       |
| Signal to Noise Ratio (S/N)    | 52dB (AGC OFF)                                               |
| Gamma Correction               | 0.45                                                         |
| Synchronization                | Internal                                                     |
| Day & Night                    | COLOR / BW / AUTO                                            |
| Electronic Shutter             | 1/60 to 1/100,000 / 1/50 to 1/ 100,000                       |
| Auto Gain Control (AGC)        | AUTO (4 Steps)                                               |
| White Balance                  | ATW / Push / User 1 / User 2 / ANTI CR / Manual / Press Lock |
| Picture Adjust                 | Mirror / Brightness / Contrast / Sharpness / Hue / Gain      |
| BLC                            | BLC/HBLC/OFF                                                 |
| Flickerless                    | ON / OFF                                                     |
| Languages                      | English / Chinese                                            |
| Privacy Mask                   | ON / OFF (4 Zones)                                           |
| Motion Detection               | ON / OFF (4 Zones)                                           |
| Mirror Function                | YES (Left / Right)                                           |
| Digital Noise Reduce (DNR)     | (2D-NR)                                                      |
| Working Temperature & Humidity | -10°C to 50°C /30% to 80%                                    |
| Storage Temperature & Humidity | -30°C to 60°C /20% to 90%                                    |
| Power(Maximum)                 | DC 12V                                                       |
| Consumption                    | 1A                                                           |

**NOTE:** ADINO TELECOM LTD reserves the right, without notification, to make changes in product design or specifications